



MAXAM FLOTXTRA

- Radial implement tire
- D speed rating allows for up to 70kph working
- Steel construction gives high durability
- Long tread life
- Excellent lateral stability
- Wide range of sizes available

Applications:



Size	LI/SS	Type	Rim (Rec.)	S.W.	O.D.	S.L.R.	R.C.	S.R.I.
			inch	mm	mm	mm	mm	
24R20.5 (605/70R20.5)	176 F	TL	AG18.00×20.5	607	1381	609	4184	-
500/60R22.5 IMP	155 D	TL	AG16.00×22.5	503	1172	527	3550	550
560/45R22.5 IMP	152 D	TL	AG16.00×22.5	543	1076	484	3260	525
560/60R22.5 IMP	161 D	TL	AG16.00×22.5	543	1244	560	3770	600
600/50R22.5 IMP	159 D	TL	AG20.00×22.5	611	1172	527	3550	550
710/40R22.5 IMP	161 D	TL	AG24.00×22.5	727	1140	513	3455	550
600/55R26.5 IMP	165 D	TL	AG20.00×26.5	611	1333	600	4040	625
650/55R26.5 IMP	169 D	TL	AG20.00×26.5	645	1389	625	4210	650
710/50R26.5 IMP	170 D	TL	AG24.00×26.5	727	1383	622	4190	650
800/45R26.5 IMP	174 D	TL	AG28.00×26.5	828	1393	627	4220	675
650/65R30.5 IMP	176 D	TL	AG20.00×30.5	645	1621	729	4910	775
710/50R30.5 IMP	173 D	TL	AG24.00×30.5	727	1485	668	4500	700
750/60R30.5 IMP	181 D	TL	AG24.00×30.5	754	1675	754	5075	800